

技术参数:


插芯:

- 插针数: 8
- 额定电流: 1A
- 额定电压: 50V
- 额定脉冲电压: 0.8kV
- 污染等级: 3
- 依据UL的额定电压: <30V
- 传输特性: 超6类可达500MHz  
依据 ISO/IEC 24 702;  
ISO/IEC 11 801
- 传输速度: 10/100/1000Mbit/10Gbit/s
- 绝缘阻抗:  $\geq 10^{10}\Omega$
- 材料: 聚碳酸酯
- 颜色: RAL 7032 (浅灰色)
- 温度范围:  $-40^{\circ}\text{C} - +85^{\circ}\text{C}$
- 依据UL 94的阻燃等级: V0
- 可插拔次数:  $>500$

Technical specification:

Inserts:

- No. of contact: 8
- Rated current: 1A
- Rated voltage: 50V
- Rated impulse voltage: 0.8kV
- Pollution degree: 3
- Rated voltage acc.to UL: <30V
- Transmission features: category 6/Class E  
up to 500 MHz; acc.  
to ISO/IEC 24 702;  
ISO/IEC 11 801
- Transmission rate: 10/100/1000Mbit/10Gbit/s
- Insulation resistance:  $\geq 10^{10}\Omega$
- Material: polycarbonate
- Colour: RAL 7032(light grey)
- Temperature range:  $-40^{\circ}\text{C} - +85^{\circ}\text{C}$
- Flammability acc.to UL 94: V0
- Mating cycles:  $>500$



订货号 Order No.

版本  
REV

重量  
weight

比例  
Scale

产品代号 Part Code

V1.0

1:1

SO-HM-RJ45-F



**浙江思美克电气科技有限公司**  
ZHEJIANG SMICO ELECTRICAL TECHNOLOGY CO.,LTD