

技术参数:




插芯:

- 插针数: 8
 - 额定电流: 5A
 - 额定电压: 50V
 - 额定脉冲电压: 0.8kV
 - 污染等级: 3
 - 绝缘阻抗: $\geq 10^{10}\Omega$
 - 材料: 锌合金 (镀镍), 聚碳酸酯
 - 颜色: RAL 7032 (浅灰色)
 - 温度范围: $-40^{\circ}\text{C} - +85^{\circ}\text{C}$
 - 依据UL 94的阻燃等级: V0
 - 可插拔次数: ≥ 500
- 插针:
- 接线方式: 冷压连接
 - 材料: 铜合金
 - 表面处理:
 - 镀银
 - 镀金
 - 接触电阻: $\leq 3\text{m}\Omega$
 - 线径范围: $0.09-0.82\text{mm}^2(28-18\text{ AWG})$
 - 剥线长度: 5mm
 - 工具:
 - 冷压钳: TL03
 - 退针器: TL08

Technical specification:

Insters:

- No. of contact: 8
 - Rated current: 5A
 - Rated voltage: 50V
 - Rated impulse voltage: 0.8kV
 - Pollution degree: 3
 - Insulation resistance: $\geq 10^{10}\Omega$
 - Material: Zinc alloy (nickel-plating), Polycarbonate
 - Colour: RAL 7032 (light grey)
 - Temperature range: $-40^{\circ}\text{C} - +85^{\circ}\text{C}$
 - Flammability acc.to UL 94: V0
 - Mating cycles: ≥ 500
- Contacts:
- Terminal: crimp terminal
 - Material: copper alloy
 - Surface:
 - hard-silver plated
 - hard-gold plated
 - Contact resistance: $\leq 3\text{m}\Omega$
 - Wire gauge: $0.09-0.82\text{mm}^2(28-18\text{ AWG})$
 - Stripping length: 5mm
 - Tools:
 - Crimp contact tool: TL03
 - Contact removal tool: TL08

 		订货号 Order No.	
		产品代号 Part Code	
版本 REV	重量 weight	比例 Scale	SO-HMGB-008-FC
V1.0		1:1	
 浙江思美克电气科技有限公司 ZHEJIANG SMICO ELECTRICAL TECHNOLOGY CO.,LTD			