


技术参数:

插芯:

- 插针数: 4
- 额定电流: 40A
- 额定电压: 830V
- 额定脉冲电压: 8kV
- 污染等级: 3
- 依据UL/CSA的额定电压: 600V
- 绝缘阻抗: $\geq 10^{10}\Omega$
- 材料: 聚碳酸酯
- 颜色: RAL 7032 (浅灰色)
- 温度范围: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- 依据UL 94的阻燃等级: V0
- 可插拔次数: ≥ 500

插针:

- 接线方式: 弹片连接
- 材料: 铜合金
- 表面处理: 镀银
- 接触电阻: $\leq 3\text{m}\Omega$
- 线径范围: $1.5\text{--}6\text{mm}^2$ (16-10 AWG)

(带管形接线端子线径范围: $0.15\text{--}6\text{mm}^2$ / 16-10 AWG)

- 剥线长度: 9_{-0}^{+1}mm

Technical specification:

Insters:


- No. of contact: 4
- Rated current: 40A
- Rated voltage: 830V
- Rated impulse voltage: 8kV
- Pollution degree: 3
- Rated voltage acc.to UL/CSA: 600V
- Insulation resistance: $\geq 10^{10}\Omega$
- Material: polycarbonate
- Colour: RAL 7032 (light grey)
- Temperature range: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- Flammability acc.to UL 94: V0
- Mating cycles: ≥ 500

Contacts:

- Terminal: spring terminal
- Material: copper alloy
- Surface: hard-silver plated
- Contact resistance: $\leq 3\text{m}\Omega$
- Wire gauge: $1.5\text{--}6\text{mm}^2$ (16-10 AWG)

(For wires with crimped ferrule, wire gauge: $1.5\text{--}6\text{mm}^2$ / 16-10 AWG)

- Stripping length: 9_{-0}^{+1}mm

					订货号 Order No.		
版本 REV		重量 weight		比例 Scale		产品代号 Part Code	
V1.0				1:1		SO-HMK-004-MQ	



浙江思美克电气科技有限公司

ZHEJIANG SMICO ELECTRICAL TECHNOLOGY CO.,LTD